



EXCESS ENERGY CELL FINAL REPORT 25 APRIL 1995

C. W. HALDEMAN, E. D. SAVOYE, G. W. ISELER, H. R. CLARK

OUTLINE

REVIEW

- RETURN TO ROOM THERMAL ENVIRONMENT • CHANGES SINCE LAST REPORT
- RE-WOUND CELL
- RESIDUAL GAS ANALYSIS


• ENERGY MEASUREMENTS

• GAS MEASUREMENTS


• CONCLUSIONS



Sealed Cell Layout



Gas Collection With Combustion Tube



SUMMARY OF CELLS ASSEMBLED

						5
RESULTS	NO EXCESS ENERGY	NO EXCESS ENERGY	5—10% EXCESS ENERGY	5—►30% EXCESS ENERGY	20—► 50% EXCESS ENERGY	20 — 1400% EXCESS ENERGY 4 x VI INPUT
C/A RATIO	520: 1	17:1	. .	5: 1	61: 1	75: 1
	PLATINIZED Ti 100 cm ²	SOFT NICKEL SHEET 3000 cm ² PLATINIZED TI 100 cm ²	SAME	PLATINIZED TI SHEET 3100 cm ²	SAME	SAME
# CATHODE	ANNEALED #41 NICKEL 1.8 lbs 52000 cm ²	SAME WIRE HEAT TREATED IN H ₂ 770°C	HARD DRAWN 0.5 mm NICKEL 16,000 cm ²	NEW WINDING HARD DRAWN 0.5 cm ² NICKEL 15,000 cm ²	HARD DRAWN - SCRATCHED #44 NICKEL 190,000 cm ² (0.002 in.) 0.05 cm dia.	#46 HARD DRAWN SMOOTH NICKEL WIRE 240,000 cm ²
CELL#		4	8	8	ო	4





OCTOBER 1994 PLANS

- USE SEALED SYSTEM RECOMBINER / CONDENSER TO COLLECT GAS
- 2. REWIND CELL WITH SMOOTH #46 WIRE
- 3. USE WET CHEMICAL GAS ANALYZER
- CONTINUE TO LOOK FOR HIGHER EXCESS ENERGY AND CHARACTER OF RESIDUAL GAS 4







RE-WOUND CELL

#46 NICKEL WIRE • CATHODE - 4.7 lbs #46 NICKl Dia. (0.00157 inch) 0.00399 cm

SURFACE AREA 240,000 cm² CURRENT DENSITY 41 μ a/cm² @ 10a

Pt PLATED Ti ANODE - 5 FOLDED SHEETS 15.2 x 20.3 cm

SURFACE AREA 3200 cm²
CURRENT DENSITY 32 ma/cm² @ 10a
75:1 CATHODE: ANODE RATIO

• ELECTROLYTE - 16 I 0.6 M K₂ CO₃ IN LAB DI WATER



GAS FLOW ABSOLUTE MEASUREMENT



• WATER BATH TEMPERATURE ± 0.1°C

• TIME MEASUREMENT ± 0.02 sec

NATIONAL WEATHER SERVICE BAROMETER - CORRECTED FOR TEMPERATURE AND LATITUDE ± 0.1 mm • BAROMETRIC PRESSURE

• MEASURED VOLUME CORRECTED FOR


- . TEMPERATURE
 - PRESSURE
- WATER VAPOR CONTENT











Value Part		•	1					e i	Lemperaluces		-						
Y P P COLO CO		ជា	EUDINE	•	;					ىد	(20 Power	£ .	Output	A Power	Quient/P.	Outsalle	Orderd a M
Column C	Man				Dielo Dielo	Erra Ban		8	म्यान्य (၁)		Correction (watte)	(*ii**)	(40110)	(wells)		(F-1)	E E
2.15	J o			(MEM)							+		07.00	2.603	133.5%	155.1%	0 73
2.835 4.68 1.153 000% 0. 254.52 0.045 0.153 0.045 0.04						,	"	150		3.753	0.0796	7.776	11.385	3.393	142.5%	161.0%	e 0
2.756 5.277 (1258) 000% 0 31453 20.202 0.071 0.000% 0 31453 20.202 0.0710 0.000% 0 31453 20.202 0.000% 0 31453	¥	2.630	4.005	14.136	100	> •	• • •	77 760		4,113	0.1125	700 /	al check	4/2		4 ·	
2.75 6.771 1.252 100%		2.803	5.014	14.605	100	5 (. •	24.013	20.202	117.9	0.1761	7.004		٧/٧	۷ / X	4 /Z	
2776 6.751 1578 1000 2570		2.758	5.128	14.138	100	.	. •	11 453	20,648	10.605	0.3006	7.658	1	W/W	٧/٢	4 i	
2.520 4.580 1.578 1.088 0.546 0.546 1.580 1.528 0.170 0.170 0.170 0.180 0	è	2.740	5.217	14.295	100 X	o	-	24.02	20.73	14.10	0.2325	6.401	666	3.697	145.3%	166.0%	
Color Colo	9	3 74.6	6.751	16.766	100%	0		34.02	10 507	4.285	0.1331	8.169	00011	4 386	121.2%	134.1%	
1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,	500		000	14.507	100 %	0	-	23.662	76.00	A 912	0.1709	20.674		2 × 1	4	M/A	
\$3.55 10.000 55.50 10.000 0 0.	<u> </u>	2.9.20		100	1001	0	-	29.662	18.73		0.2416	20.394		i i	77 77	122.6%	0.70
\$ 3.55	. O.	3.367	010.01		100	•		30.62	20.63/		1986	24.681	20.043	3.362		170.8%	0.0
2.15	202	9.380	10.00	35.06	200	٥		30.455	20.52			991 4	12.2	4.032		4/2	
2.319 4.565 15.38 1000 2.2013 18.882 6.156 0.250 0.250 1.7014 Weakward and MIA Williams and	603	3.488	11.500	40.1	2 20			24.184	10.78	4.404	200		12,208 W heaters at	ď Ž	i i	4/2	
2.889	2	2.910	4.008	7.00	2 2 2			28.013	19.862	6.161	0000		1,718 W heaters ad	٧ ٢	¥/R	20.7 0%	0.0
2.450 2.779 6.257 00% 0 2.240 19.545 2.757 0.1102 2.220 N Passwa and NIA	· 2	2.758	4.645	12.535	2 0 0			24.726	20.36	4.366	0.505.0		9.99	3.170	40.00		
2.5450 2.789 6.285 0.00% 0 22.620 19.544 2.875 0.1072 3.250 1.00% What was a mine of the control	200	2.869	4.766	13.679	200	•		21.0	19.516	2.384	0.1156		de stated W coc c.	۷ ۲	4 / X		
2.550 2.577 6.525 100% 0 22.467 10.525 10.00% 0 22.47 10.255 10.000 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.255 10.00% 0 22.47 10.00		2.630	2.766	7.275	100	•		22 A20	19.964	2.876	0.1212		September 1	۲ <u>۱</u> ۲	۲ ۲	£ :	
2.55 2.55 8.45 100% 0 22.47 19.25 2.86 0.107 13.31 1.007 13.24 132.4% 132.2% 132.4% 132.2% 132.		2 640	2.570	6.626		> '		100 50	10.671	4.336	0.0003		200	4/2	4 / 1	4 / H	
1.00 1.00	90	663.6	2.676	6.626		0		23.60	10.625	2.862	0.1172					į	9,
Color Colo	002	44.6	2.676	6.602		0		7667					91.100	4.924	132.4%		
1.00		7.00.7	10	-					1000	7.100		_		4 4 78	120.0%	142.0%	20
1,220 1,000 2,000 20% 0 2,000 1,		3	7 904	26.407				26.603	444	A 072		_	10.47	96	\$67.3%	4) II	90
1,000 2,000 20% 6 2 2,1165 19.07 0.0000 2.795 6.185 3.300 227.3% 1.900 2.000 2.000 2.000 2.000 2.705 2.216 0.00004 2.221 2.216 0.00004 2.221 2.216 0.00004 2.221 2.216 0.00004 2.221 2.216 0.00004 2.221 2.216 2.200 2.221 2.200 2.221 2.200 2.221 2.200 2.221 2.200 2.221 2.200 2.221 2.200 2.221 2.200 2.221 2.200 2.221 2.221 2.200 2.221	302	3.220	7.003	25.448				28.617		1.42			3.026	2.4.4	\$1.095	4/N	2.08
1,000 2.705 2.000 2.00 2.00 2.1155 10.007 2.211 0.0000 2.705 0.105 1.000 2.705 2.105 2.2	303	3.220	200	2 000			7.	21.069	000.01				4.155		221 3%	4 12	1.20
Upper 1, 0.25 1.0.25 1.0.25 1.0.25 1.0.25 1.0.25 1.0.25 2.0.25	304-low P	9.0	Z. 30	000		•	7 .6	21.165	700.01				6.185	0.0	124 54	136.4%	0.72
2.046 2.174 2.094 2.2246 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 1.275 0.004 0.004 1.275 0.004 0.004 1.275 0.004 0.004 1.275 0.004 0.0	COLNER P	1.023				•	9.3	22.158	10.01	7.7			18.601	3.663	36.036	4 2	1,51
2.046 2.054 2.027 20% 6 2.6 21.081 10.075 2.27 0.0050 1.292 2.004 2.730 2.730 2.730 2.730 2.730 2.730 2.730 2.730 2.730 2.730 2.730 2.204 2.207 10% 6 2.6 21.786 20.564 1.292 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 1.392 0.0050 0.664 0.792 0.292 0.666 0.390 0.664 0.792 0.292 0.0050 0.664 0.792 0.292 0.666 0.390 0.664 0.792 0.292 0.666 0.390 0.664 0.792 0.292 0.666 0.390 0.664 0.792 0.292 0.666 0.390 0.664 0.792 0.666 0.390 0.664 0.792 0.666 0.390 0.664 0.792 0.665 0.666 0.390 0.664 0.792 0.665 0.666 0.390 0.664 0.665 0.666 0.390 0.664 0.665 0.666 0.390 0.664 0.665 0.666 0.390 0.664 0.665 0.666 0.390 0.664 0.665 0.666 0.390 0.666 0.390 0.666 0.390 0.664 0.665 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0.666 0.390 0	306	2.080		9.4				27.004	20.336	9.00			6.116	3.762	20.007	4 / 8	1 63
1,000 1,00	A308a	3.160					7 .9	21.001	10.775				4.029	2.736	200	4/4	1.62
1,002 2,220 2,462 20% 6 2.6 21,266 10,849 1,439 0,000 0,684 3,33 2,264 448,0% 1,000	A307	2.046					7.	21.481	20.004	100.			3.08	2.661	40.0%	1	2.43
1,002 1.00 1.373 1.226 2.206 2.1706 20.504 1.202 0.0004 Vibrative ab MA MVA MVA 1.002 1.001 1.00	n308	1.067		7.60		•	2.6	21.288	10.940	1.43			3.33	. 2.646	487.0%	È	¥ ×
1,802 1,803 1,373 10% 2.6 22.395 20.182 2.213 0.0024 0.550 2.491 1.941 452.9% 3.216 1.371 10% 0.206 0.695 0.0024 0.707 2.203 2.216 4.31.% 3.216 1.371 10% 0.206 0.695 0.0024 0.707 2.023 2.216 4.31.% 3.216 1.371 1.986 0.278 0.470 0.004 0.707 0.0017 0.134 2.005 0.896 1.940 0.486 1.00% 0.21.65 1.900 0.21.65 0.0015 0	900	1.033		2.40			9 6	21,796	20.594	1.20					۲ ۲	e :	9.6
1,784 1,853 1,428 10% 0 2.0 0 0.005 0.00	910	1.802		1.373				22,305	20.182	2.21.					452.0%	4	
1,862 1,137 10% 6 20.69 1,871 1,053 0,0064 0,707 0,134 0,134 1,871 1,898.6% 33 1,884 0,272 0,134 0,1		1 704		1.426		-	9 (20,603	20.608	0.80		_		2 2 1 6	413.1%	625.3%	
1,080 0.099 1,040 100% 0 1,050 1,050 0.117 0.0017 0.134 0.005 0.108	- 12	1 7.87		1.13					10 437	1.05			50.7	1 871	1406.6%	3382.61	_
1.664 0.276 0.467 100% 0 21.551 10.306 1.753 0.0015 0.106 1.000 W heaters and 1.470 103.1% 1.662 0.276 0.467 100% 0 21.751 10.306 2.465 0.0015 0.202 3.000 W heaters and 1.470 103.1% 2.106 0.276 0.466 100% 0 21.253 20.247 1.106 0.0142 1.560 2.000 6.500 2.407 100.0% 1.26.7 100% 0 22.247 1.106 0.0142 1.560 2.000 1.00% 1	2 IEW							60.00	710	0 71			c00.7		4	4 / x	< 2
1.682 0.276 0.467 100% 0 21.351 19.302 2.465 0.0015 0.202 3.000 W heatered of 1.470 103.1% 2.162 0.276 0.466 100% 0 21.352 20.247 1.166 0.0142 1.569 3.066 1.470 160.0% 2.2.06 1.00% 0 21.352 20.247 1.106 0.0142 1.569 3.066 2.407 10.104 101.0% 2.2.06 10.660 2.301 0.0256 4.102 6.659 2.407 10.104 101.0% 2.643 3.657 20.000 70.140 100% 0 20.490 1.6.74 2.369 0.0162 5.000 6.304 2.643 1.00% 0 20.490 1.	,							10.03					1.000 W Neader		4 /2	W/W	₹
1,886 0.276 0.486 100% 0 21.785 19.300 1.00 0.0142 1.589 3.086 1.477 100.0% 2.180 0.0142 1.589 3.086 1.477 100.0% 2.180 0.0142 1.002 6.100 0.0142 1.002 6.100 0.0142 1.002 1.004 100% 0 2.206 19.480 0.0142 5.080 6.539 1.449 12.85% 1.449 12.8	150							21.15	96.91			_	S. 998 W heaters a		*	230.22	2.0
2.150 2.002 4.304 100% 0 22.06 10.660 2.391 0.0256 4.102 6.650 2.407 101.0% 22.06 10.660 2.391 0.0256 4.102 6.4021 1.014 101.0% 22.05 10.660 2.391 0.0256 6.4021 1.014 101.0% 22.05 10.40 100% 0 22.05 10.40 100% 0 21.040 100% 0 21.040 100% 0 21.040 100% 0 2.051 10.574 2.369 0.0142 5.090 6.539 1.440 1.265% 4.109 2.2693 1.476 0.0046 0.0046 0.0056 4.109 2.256 4.750% 1.016 3.266 2.209 1.007 100% 0 2.673 10.406 0.0046 0.0056 4.109 2.256 4.720% 1.016 3.266 2.209 1.016 3.266 4.720% 1.016 3.266 4.720% 1.016 3.266 4.720% 1.016 1.007 100% 0 2.673 10.406 1.0046 0.0046 0.0046 0.0046 2.006 1.007 4.220% 1.016 1.007 100% 0 2.673 10.746 1.007 0.0040 1.007 4.220% 1.016 2.001 1.007 100% 0 2.001 10.74 1.007 100% 0 2.001 10.74 1.007 10.0040 1.007 1.0	3 15	00.						21.785	16.300				3.068	7.4.		177.6%	67.0
2.150 2.002 2.301 10.14 10.197 22.06 16.669 2.391 2.301 64.021 1.014 101.974 2.301 2.001 10.007 0.0105 0.01	91Cnu	0. 0.					•	21.353	20.247				6.699	2.407		***	
2.626 3.680 9.040 100% 0 21.943 19.574 2.369 0.0162 5.090 8.539 1.449 128.5% 2.643 3.167 0.000 70.140 100% 0 21.943 10.574 2.369 0.0162 5.031 8.324 2.693 147.0% 2.543 3.167 0.000 5.631 4.109 3.264 400.0% 2.543 3.167 0.000 5.631 4.109 3.264 400.0% 2.775 3.090 11.007 100% 0 2.6 21.321 19.836 1.768 0.00046 0.056 4.109 3.266 2.239 310.7% 1.834 2.100 11.007 100% 0 2.6 2.0673 19.400 0.704 3.665 2.000 2.010 1.601 100% 0 2.6 21.143 19.74 1.307 0.00046 0.074 2.60 2.001 1.007 100% 0 2.0 21.143 10.762 1.004 0.0004 0.074 2.60 2.001 100% 0 2.0 21.143 10.0115 5.430 0.0105 2.610 1.001 10.010 0.0004 1.001 0.700 2.010 1.001 10.010 0.0004 1.001 0.700 2.010 1.001 1	71Cm	2.2 2						22.06	10.660				64.021	1.014			_
\$1067 20,000 70.140 10074 0 21.943 10.574 2.369 0.0192 5.631 8.324 2.603 147.0% 2.643 3.167 8.064 100% 0 23.616 20.601 3.014 0.0300 5.631 4.109 3.264 400.6% 2.776 3.089 11.087 100% 0 2.6 21.321 19.836 1.766 0.0046 0.666 4.109 3.266 2.239 310.7% 1.812 2.084 1.897 100% 0 2.6 20.673 10.406 1.176 0.0035 1.016 3.266 2.239 310.7% 1.834 2.185 1.763 100% 0 2.6 20.673 10.406 1.176 0.0044 0.704 3.666 2.001 2.004 1.809 2.019 1.601 100% 0 2.6 21.143 19.746 1.387 0.0044 0.874 4.268 2.891 2.851 2.651 1.001 1.834 2.185 1.703 100% 0 2.6 21.143 19.746 1.387 0.0044 0.877 4.268 2.891 2.851 1.75.7% 1.836 3.067 2.876 100% 0 3.0 21.206 19.762 1.644 0.0044 0.877 0.548 2.891 140.1% 2.169 8.218 7.901 100% 0 4.0 23.383 19.931 3.462 0.0115 5.430 1.829 331.8% 2.326 8.218 7.901 100% 0 4.0 24.601 10.01 0.0041 0.790 2.819 1.0831 100.3% 2.326 8.829 13.418 100% 0 2.8 21.27 20.328 0.0442 0.0041 0.790 1.8310 1.0834	un316	2.62						38.979				_	6.539	1.440			
2.643 3.167 6.064 100% 0 23.616 20.601 3.014 0.0300 5.531 4.109 3.264 460.6% 2.776 3.089 11.087 100% 0 2.6.731 19.836 1.776 0.0035 1.018 3.749 2.236 319.7% 1.812 2.084 1.897 10% 1 2.6 20.673 19.496 1.175 0.0035 1.018 3.749 2.965 472.0% 1.834 2.185 1.763 10% 4 2.6 21.143 19.746 1.387 0.0046 0.074 3.685 2.081 226.1% 1.809 2.019 1.601 10% 6 2.6 21.143 19.746 1.387 0.0046 1.677 4.268 2.091 2.541 1.75.7% 1.824 2.129 1.700 10% 6 3.0 21.296 19.762 1.644 0.0069 1.677 6.541 4.111 175.7% 2.169 8.218 7.901 10% 6 4.0 23.383 19.931 3.462 0.0115 5.430 0.089 2.819 1.829 331.8% 2.326 8.899 13.419 10% 6 4.0 24.601 1.981 4.991 0.0163 0.080 2.819 1.081 1.081 1.081 1.083 1.083% 2.326 8.899 13.419 10% 6 2.6 24.601 1.981 0.091 0.790 2.819 1.083% 2.819 1.083% 2.326 8.899 13.419 10.83% 2.326 8.899 13.419 10% 6 2.6 24.601 1.981 0.0391 17.236 1.8319 1.083%	9164.	3.06						21.043					8.324	2.603			
2.776 3.000 11.007 1007 1007 1007 1007 1007 100	000	2.64						23.615					4.109	3.264			
1,812 2.084 1.887 10% 12 2.8 20.873 19.486 1.175 0.0035 1.018 3.749 2.965 472.0% 1.834 2.188 1.763 10% 12 2.8 21.05 19.886 1.395 0.0046 0.794 3.886 2.891 2.891 442.1% 1.805 2.019 1.601 10% 8 2.8 21.143 19.746 1.397 0.0040 0.874 4.288 2.891 254.8% 1.824 2.129 1.700 10% 8 3.0 21.296 19.762 1.544 0.0066 1.677 4.288 2.891 254.8% 1.935 3.067 10% 8 4.0 23.383 19.931 3.462 0.0163 9.886 13.849 3.883 1.601% 8 4.0 24.801 19.81 4.991 0.0163 9.886 13.849 1.829 331.8% 2.326 8.899 13.418 10% 8 4.0 24.801 19.81 4.991 0.0163 9.886 13.89 1.831 1.081 108.3% 2.326 8.899 13.418 10% 8 2.8 21.27 20.328 0.942 0.0391 17.236 18.319 11.081 108.3%	200	2.77		_			•	121.16					1 28A	2,238			
1.834 2.186 1.763 10% 12 2.0 21.05 10.866 1.365 0.0046 0.794 2.881 2.981 442.1% 1.808 2.019 1.801 10% 4 2.8 21.143 19.746 1.397 0.0040 0.874 3.885 2.881 254.8% 1.824 2.129 1.700 10% 6 3.0 21.296 19.762 1.844 0.0066 1.677 4.268 2.881 254.8% 1.935 3.007 2.875 10% 6 4.0 23.383 19.931 3.462 0.0165 5.430 9.541 4.111 175.7% 2.159 6.218 7.901 10% 6 4.0 24.801 10.0163 0.806 13.849 0.0941 0.790 2.819 1.829 331.8% 2.326 8.589 13.418 10% 6 4.0 24.801 10.81 0.0041 0.790 2.819 1.081 108.3%							•	20.073					2 740	2.966			
1.808 2.019 1.601 10% 4 2.8 21.143 19.746 1.387 0.0040 0.874 2.288 2.081 256.8% 1.802 2.019 1.700 10% 8 2.8 21.143 19.752 1.664 0.0066 1.677 4.288 2.081 1.75.7% 1.936 3.057 2.876 10% 8 4.0 23.383 19.931 3.462 0.0115 5.430 9.541 4.111 175.7% 2.169 0.0163 9.886 13.849 3.083 140.1% 2.169 10.1% 8 4.8 24.801 19.81 4.891 0.0163 9.886 13.849 3.083 1.683 1.083	22CUN						9.7							2.001			-
1,824 2,129 1,700 10% 6 3.0 21,296 19,762 1,644 0,0066 1,677 2,676 9,541 4,111 175,7% 1,984 3,067 2,676 10% 6 3,0 21,296 19,931 3,462 0,0115 5,430 9,541 4,111 175,7% 2,1676 3,063 1,001 10% 6 4,0 24,801 19,81 4,891 0,0163 9,866 13,848 3,800 10% 6 2,8 21,27 20,328 0,941 0,790 2,818 1,829 331,8% 2,326 8,899 13,418 10% 6 2,8 21,27 20,328 0,9391 17,236 18,318 1,081 108,3%	Sun323					*	, i							2.601			
1.936 3.067 2.876 10% 6 3.0 23.383 19.931 3.462 0.0115 5.430 5.39 2.169 6.216 7.901 10% 6 4.0 24.601 19.81 4.991 0.0163 0.666 13.849 3.963 140.1% 2.326 6.889 13.416 10% 6 4.6 24.601 19.81 0.942 0.0041 0.790 2.819 1.629 331.6% 2.326 6.889 13.416 10% 6 2.6 21.27 20.326 0.942 0.0391 17.236 18.319 1.083 1.08.3%	Hunde					*			_		۰			4.111			
2.169 6.216 7.901 10% 6 4.0 24.601 19.01 0.0163 0.666 13.649 3.991 31.6% 2.326 8.599 13.416 10% 6 4.0 24.601 19.01 0.942 0.0041 0.790 2.610 1.629 331.6% 2.326 8.599 13.416 10% 6 2.6 21.27 20.326 0.942 0.0391 17.236 18.316 1.081 106.3%	Humaza Populari					*	9 6		•		0	<u></u>					•
The num ro. acidemaily supposed 10% 6 4.8 24.801 19.81 4.801 0.0163 0.042 0.0041 0.780 2.819 1.829 331.8% 2.326 8.889 13.416 10% 6 2.6 21.27 20.326 0.942 0.0041 0.780 16.316 1.081 1.083 1.08.3%	Hundre					• *	.	77.76					•	640 6			
2.326 8.659 13.416 10% 6 4.8 21.27 20.326 0.942 0.0041 0.790 2.51 1.061 1.06.3%	í			peop										1 828			
1000 10% 6 2.6 2.1.6 1.0.00 17.236 18.316 1.0.236 18.316	_			13.4		ž	9.	•									(e) — y
2,034	Aunaza					į	N					_					

						1						
		•	The Following Runs are th	•	and of Exper	e e e e e e e e e e e e e e e e e e e			Shart of Experiments with the new Smacour recommend	_		Data Taken Over
				i	ā		8	P orfice	17	Flowrele (cc/min)	Efficiency	Time Bance
To Name	(Torr)	HAC PERMUTA (Torr)	(p ⁴)	리 (ge	Z (§	1 (§	=	(beled)	(2)	(hully corr.)		(win)
	mon Berocell)	(calibrated)							20 641	47.20	64.29%	1250-1350
37.7	787.20	759.66	0.6032	0.8013	15.27	0.4896	19.10	0.0547	19.747	48.11	85.60%	3200.3600
	766,62	750.30	0.7183	0.7202	15.37	0.6555	- 60 41	0.0616	20,031	14.81	77.98%	2000-2200
287	745.01	730.31	0.7753	0.7777	15.05	0.75		0.000	20.522	47.58	81.36%	1650-1700
Pun 200	766.65	750.33	0.0375	0.0405	19.60	0.07	15.33	0.0648	20.443	53.60	83.27%	1050-1100
Dist. 280	767.68	760.32	0.7066	0.7093	15.38	0.0443	15.35	0.0586	19.740	47.31	84.42%	3600-3700
280	758.43	751.43	0.7775	0.7604	15.28	0.7218	3.64	0.00.0	19.725	95.90	85.46%	7200-7500
3	771 06	763.56	0.5420	0.5451	15.28	0.4612	15.20	0.003	20.856	96.63	86.30%	1300-1400
	765.75	756.48	0.6049	0.6072	15.25	0.4805	21.61	0.160	20.525	111.08	86.86%	1250-1350
Run292	774.78	766.16	0.7184	0.7209	15.51	0.5830	15.37	0.00	10.05	47.95	85.58%	2000-2100
Rucks	174.00	767.28	0.4375	0.4395	16.25	0.3757	5.18	0.0636	988	42,26	62.93%	2500-3000
HUNDE	77.00	767.25	0.6714	0.6737	15.48	0.5051	15.40	0.0786	20.500	45.81	85.71%	950-1030
Run283	756.70	749.65	1,1130	1,1160	15.50	1.0363	15.51	0.00	10 580	26.35	91,43%	5000-6000
Function	77.9.70	771.87	1,0230	1.0260	15.02	0.0401	13.63	0.076	20.201	24.55	84.02%	1230-1315
Pun 207	2.00	74.70	1.0690	1.0720	15.65	0.6843	15.57	7770.0		23.58	81.66%	1800-2200
Rw26	166.40	94.46	0.9629	0.9659	15.67	0.8648	15.59	0.0811	10.043	23 66	81.90%	3500-4000
Runzoo	769.11	90.10/	1 0940	1.0970	15.83	1.0263	15.75	0.0707	2/2/20			
Run300		10.50								78.57	86.40%	1900-2200
Purchol - Data Lost due	•	747 A3	1,3088	1.3110	15.94	1.2235	15.85	0.0875	19.033	46.77	A7 34%	1150-1250
Aur302	765.00	00.101	.2 5190	.2.5200	12.20	.2.5824	12.25	0.0424	19.960	67.0	97.75%	5000-5150
Rundos	775.04	779.00	-8.2970	.6.2870	6.61	.0.4103	6.40	0.1313	10.060		37.48%	2400-2800
Purcot-los P	779.86	749 64	0000	7.0210	21.40	6.8746	21.34	0.1464	20.08		35.74%	1900-2000
Purcot High P	756.59		7380	.5, 7360	9.15	.5.6569	9.03	0.1200	20.183	6.4	90 A 8 4 8 4 8 4 8 4 8 4 8 8 8 8 8 8 8 8 8	1272-1325
Runsos	770.35	56.17	1900	0.9071	15.68	0.8700	15.64	0.0371	20.661	9.6	34.75%	1800-2000
Purcole	773.07	765.50	0.3967	0.4207	15.19	0.4176	15.10	0.0031	20.110	70.7	23 98%	2800-2900
Rundo7	773.04	140.04	0.4164	0.4155	14.87	0.4135	14.87	0.0020	20.270	,	13.04%	3260-3660
Rundos	755.01		10010	0.4091	16.18	0.4071	15.16	0.0020	20.184		26.41%	600.600
Aun300	771.98	764.40	977	0.4144	16.05	0.4130	15.06	0.0014	21.043	o (22.15	A 50 - 7 50
Russio	765.66	756.38	27.7	0.4146	14.60	0.4134	14.00	0.0012	20.422		22.72	980-1040
Aus 11	757.22	720.27	7	24163	15.23	0.4155	15.23	0.000	20.064		20.02	1200:3600
Bus 12	775.36	767.70	0.4157		14.02	0.4144	14.92	0.00.0	10.936	9.12	40.40	7500-8000
Rw313	758.36	751.36	0.4196	0.4224	15.09	0.4219	15.00	0.0005	10.422	7.52		
Rung14	787.17	759.63	0.4216	30.0	15.28	0.3943	15.28	0.0003	19.535	2.08	90.00	
Purd 16s	779.08	771.27	0.3837	9.55	16.22	0.4115	15.22	0.0001	19.405	1.07	417.50	
9,4314	175.02	767.37	0.4108	0.4116	13.64	4123	15.11	0.0045	20.453	10.55	87.11%	
	769.10	761.60	0.4158	0.4166	21.61	2003	41.51	0.0100	19.767	34.30	85.47%	-
	762.60	755.44	0.6095	0.6099	2.6	0.000		ט זען	20.295	189.00	84.30%	
	760.02	753.62	0.2108	0.2115	14.76	0.04/8		200	10.779	22.10	62.48%	3600-3600
RUNGIN	766.02	746.16	0.7814	0.7829	16.22	0.6605	71.61		20 746	37.54	83.74%	1200-1500
Punko	10.007	761.10	0.6103	0.6116	15.11	0.4812		9000	10 078	6.20	26.68%	1600-2200
Runge	741.76	754.62	. 0.2201	0.2211	14.70	0.2186		0.0023	10 701	5.47	22.33%	•
Rundzz	44.07	781.28	0.8840	0.8860	15.58	0.8837	00.0	0.00	010 01	8.02	26.60%	
Rundza	762.60	746.83	0.2017	0.6660	15.20	0.6636	13.40	0.000	19 927	8 . 18	26.01%	
Auto.	764.00	767.44	1.2460	1.2470	16.67	1.2448		0.00	10.076	9.00	25.04%	400-600
Runaza	758.18	751.10	0.3682	0.3664	4.86	0.3641		200	20.149	16.04	25.66%	2000-2200
Purces	7.57.86	750.90	2.5690	2.6660	17.08	2.5649	90./-					-
Runge/	Almonda	eldboed			1			0.00	10.700	25.46	26.51%	
	742.90	766.73	3.1200	3.1280	7.7.	3.21.6		0.0023	20 607	90.0	26.63%	
Runde	774 31	700.00	0.0036	0.0050	20.70	900			***	82.27	4/6/10	4600-5200
							41 11	4500				



بز	5




.

Oxford (************************************	0.64 0.62 0.67 1.11 1.11 0.07 2.63 2.63 2.63 0.07 0.07 0.79	
DAIDAUTE DA	121.1% 110.0% 305.3% N/A N/A N/A N/A N/A N/A N/A	
Outsuile:	114.9% 112.0% 362.0% 211.3% 157.0% 126.3% 106.1% 498.2% 131.0% 134.6% 106.7% 1019.6%	
A Ported (walts)	2.084 1.855 1.217 2.303 2.301 2.312 1.303 1.170 3.367 2.950 3.407 1.702 2.530	
Output Power (watte)	16.049 15.486 1.661 4.372 6.563 11.73 6.26 20.391 4.213 12.458 13.205 27.037 2.605	
foet_losid)	13.65 13.631 0.464 2.069 4.192 0.416 4.957 19.221 0.846 9.508 9.706 1.25.335 0.275	
HZO Parest Correction (wells)	5.77 0.0472 5.51 0.0355 5.56 0.0064 1.262 0.0066 1.235 0.0306 2.269 0.0306 2.269 0.0306 3.294 0.0693 4.406 0.0317 4.406 0.0317 4.702 0.0265 9.591 0.0023 1.01 0.0023	
40	40 -44	
Amblera. (C)		
ਰ ਹ	25.716 25.156 20.774 22.352 22.352 21.884 27.271 24.323 24.323 24.323 24.627 22.659 27.208	
Eng Esek Y	(Voits)	
outy Diele	100% 100% 100% 20% 20% 20% 20% 20% 20% 20% 20% 20%	
e u	25.146 24.784 1.932 3.947 7.189 14.130 7.211 28.354 1.599 14.370 34.014 0.700	
_	Ampa) 7.032 7.019 0.001 My eMppe 1.162 7.869 6.810 11.266 11.266 11.266 11.266 11.266 11.266 11.266 11.266	
×	3.576 7.032 25.146 3.531 7.019 24.784 1.950 0.991 1.932 2.01 3.162 3.947 2.220 4.907 7.188 2.403 7.969 14.130 2.139 6.819 7.211 2.99 11.266 28.364 1.799 2.027 1.599 2.494 8.103 14.397 2.494 8.103 14.397 2.906 14.927 34.014	
4/20/9 5 is Name	Un332wet IId 3.576 7.032 4 Un332wet IId 3.531 7.019 2 Un332wet IId 3.531 7.019 2 Un335wet IId 1.960 0.991 2.021 Un335wet IId 2.061 3.182 Un335wet IId 2.081 7.989 1.289 Un340bwet IId 2.189 6.819 Un340bwet IId 2.189 6.819 1.286 1.034 2.199 2.027 2.479 8.110 2.479 4.110 2.479 8.110 2.479 8.110 2.479 8.110 2.484 8.103 2.404 8.103 2.403	



•			•
Deta Takan Over <u>Jima Banos</u> (min)	3300-3800	6600-7200	3000-3600 3200-3500 2500-2600 3400-3600 1800-2000 1800-2000 2500-2600 2500-2600 2600-2600
Peradey Efficiency	92.75%	90.60%	39.28% 40.36% 38.64% 25.31% 24.73% 36.70% 36.70% 33.04% 91.47%
Flowrate (cc/min) (fully corr.)	73.11	10.85	14.01 22.20 34.52 16.51 66.76 5.62 35.34 91.60 3 19
ដឲ	20.186	19.833 20.443	20.067 20.235 19.906 19.849 20.010 20.086 20.102 20.341 20.341 20.466 20.509
P orthor (poled)	0.0200	0.0156	0.0938 0.0974 0.0120 0.0222 0.0306 0.0078 0.0199 0.0023
g (sed	18 20	20.69	15.53 15.22 16.22 15.04 15.04 15.44 16.05 16.16
27 (g) eq	0000	5.6552 1.6165	0.6300 0.5442 2.2244 0.04163 0.5442 0.5845 0.3862 0.3963 0.410 0.4001
19 (g)		20.71	15.63 15.32 16.63 15.06 15.06 15.20 15.24 16.24 16.24
되 <u>(</u>		5.7100 6.8710 1.8200	0.7238 0.7238 0.0548 0.0548 0.0548 0.2458 0.8482 0.3381
Jeg (open)		3.7150 6.8730 1.6160	0.7216 0.6398 0.0534 2.2250 0.4369 0.6167 0.2439 0.9456 0.4704
Ber. Promuro	(cellbrated)	761.69	_
Chemical Lynn	(Torr) (hom Berocell)	750.06 776.38	Junisassiane 64 757.86 Junisassiane 64 767.86 Junisassiane 184 780.10 Junisassiane 184 770.28 Junisassiane 184 770.28 Junisassiane 184 766.41 Junisassiane 184 762.89 Junisassiane 184 763.89 Junisassiane 186.43 Junisassiane 186.38
4/20/8 S	New Mer)	Aun332/wet 11d Run333/wet 11d	Runssbaret lid Runssbaret lid Runssbaret lid Runssbaret lid Runssbaret lid Runssbaret lid Runssbaret lid Runssbaret Runssbaret Runssbaret Runssbaret Runssbaret Runssbaret Runssbaret Runssbaret Runssbaret Runssbaret







MASSACHUSETTS INSTITUTE OF TECHNOLOGY LINCOLN LABORATORY

2 May 1995

TO:

Ad Hoc Committee Distribution

FROM:

C. W. Haldeman Will

SUBJECT:

Additional Material

You should have all received my viewgraphs from the 25 April meeting. At that meeting Marv and Ron requested that I replot the data from the new cell (Cell 4) in terms of excess power vs. net input power. This has been done and is attached. The large scatter seems to indicate that the excess power is not a function of net input or at least has a stronger dependence on some variable not controlled. Also requested and included is the old data from Cell 3 which includes variable not after the power failure. The calibration curve is the same for both windings of the cell and includes both calibration and recalibration results.

Since the data now includes both Cell 3 and 4, I replotted the Cell 4 results to avoid confusion. This is the same plot in the presentation which was entitled "Electrolytic Cell Data Results." Please add these figures to the package.

CWH:jf Attachments


9 20 Cell 3 Data Results Input Power (Watts) 30 20 Dead Cell Data Live Cell Data -Calibration S 0 9 20 Cell - Amblent Temperature (C)

30 25 Cell 4 Data Results Net Input Power (Watts) **Pulsed Runs** Calibration DC Runs 0 S 9

Cell - Ambient Temperature (C)















GAS MEASUREMENTS

- CHEMICAL ABSORPTION
 BURRELL WET ANALYZER
- INFICON QUADRAPOLE 102 VOLT ENERGY MASS SPECTROMETER
- CRYO CONDENSATION

Mercury Filled Gas Collection Vessels Mercury / Catch Basin Gas Recombiner Water Cooled H20 Drain Tube, Flash Suppressor Gas Line From Çell

Electrolytic Cell Current Gas Collection System











BURRELL ABSORPTION TUBE ANALYZER GAS WET ANALYSIS

GAS TESTED FOR

ABSORBENT

 CO_2

CrCl2 sol

KOH sol

02

HOT (300°C) CuO

V

~ H

WET ANALYSIS RESULTS

PERCENT

SAMPLE	CO ₂ O ₂	02	Н2 В	RESIDUE
AIR	0	21		43
RAW CELL GAS	0	32	29	01
RECOMBINED CELL GAS MANY SAMPLES	0	1822 00.2	00.2	BALANCE 78——82 CALLED PROCESSED CELL GAS

MASS SPEC ANALYSIS OF PROCESSED CELL GAS SHOWS N₂, A, H₂O

HYDRO-CATALYSIS CLAIMS TO HAVE FOUND 1-2% H₂







• GAS GENERATION


2 TO 100 cc/minute 2.8 TO 144 l/day

• RECOMBINED WATER CHECKS OUT GAS MEASUREMENT

• RESIDUAL GAS FROM RECOMBINER - 50 — 100 cc/day - 1.8% TO 0.1% OF TOTAL GAS FLOW - NEARLY 100% CONDENSED OVER LN2







"RAW CELL GAS"

五せりようていりま

4

9


S

2

3






















ISOTOPIC RATIOS - HD/H2

SAMPLE	TEST PRESSURE TORR	3/2 RATIO
BOTTLE HYDROGEN	1.3 × 10 ⁻⁴	0.052
LAB DI WATER	9.8 × 10 ⁻⁵	0.035

LAB DI WATER



0.044 9.9×10^{-5} CELL ELECTROLYTE







WHAT TO DO NEXT FOR HIGHER ENERGY

• STUDY GAS CELL WHICH HAS MUCH HIGHER ENERGY DENSITY - HYDROCATALYSIS WILL PAY -- CRDA?

• TEST PALLADIUM - SILVER COATED NICKEL WIRE WITH D2 O SYSTEM ACC CONTINUATION? •INVESTIGATE TUBULAR REACTOR USING PALLADIUM - SILVER



CONCLUSIONS

• EXCESS ENERGY IS PRESENT AT 0.5 TO 5 W LEVEL 0.5 TO 2.5° ABOVE CALIBRATION

TEMPERATURE CALIBRATIONS ± .02°C

• GAINS ARE HIGH 5 TO 14 × NET INPUT 1.5 TO 4 × GROSS VI INPUT

BUT ONLY AT 1-4 W EXCESS

- SOURCE IS NOT DETERMINED
- LOWER STATE HYDROGEN WAS NOT FOUND WHY?
 - A) NOT THERE
- CHEMICALLY MORE REACTIVE THAN REPORTED **EASILY ABSORBED IN METAL**
- ISOTOPIC RATIOS CONSISTENT WITH ELECTROLYTIC CELL **DECOMPOSITION OF WATER**
- CANNOT PROVE OR DISPROVE POSSIBLE EXPLANATIONS **FOR EXCESS HEAT**



